

10  
20  
30  
40  
50  
60  
70  
80  
90  
100  
110  
120  
130  
140  
150  
160  
170  
180  
190  
200  
210  
220  
230  
240  
250  
260  
270  
280  
290  
300  
310  
320  
330  
340  
350  
360  
370  
380  
390  
400  
410  
420  
430  
440  
450  
460  
470  
480  
490  
500  
510  
520  
530  
540  
550  
560  
570  
580  
590  
600  
610  
620  
630  
640  
650  
660  
670  
680  
690  
700  
710  
720  
730  
740  
750  
760  
770  
780  
790  
800  
810  
820  
830  
840  
850  
860  
870  
880  
890  
900  
910  
920  
930  
940  
950  
960  
970  
980  
990

1. A system for non-contact dimensional measurement of a workpiece, comprising:

a processor;

a memory coupled to the processor and including a sensor arm module, a sensor head module, and a wireframe module;

5 a sensor arm movable in lateral, longitudinal, and transverse directions and in communication with the processor; and

a sensor head coupled to the sensor arm, the sensor head including,

a light source for producing a light to contact a surface of the workpiece, and

a detector for sensing a portion of reflected light from the workpiece, the detector generating a signal indicative of the proximity of the workpiece,

wherein the sensor arm and head modules direct the sensor arm and sensor head to perform proximity measurements along three parallel, lateral tracks extending along a longitudinal length by moving the sensor head in proximity to and continuously along each lateral track,

15 wherein the wireframe module determines the diameters of the workpiece along the longitudinal length based on the proximity measurements and generates a workpiece profile.

2. The system of claim 1, wherein the light source comprises a laser light diode.

20 3. The system of claim 1, wherein the wireframe module determines the location of a crown of the workpiece based on the diameters.

4. The system of claim 1, wherein the sensor head further comprises a roughness detector configured to receive a second portion of reflected light and generate a signal indicative of the roughness of the surface of the workpiece.

5 5. The system of claim 1, wherein the detector generates signals indicative of the proximity of the surface of the workpiece based on the intensity and position of the portion of the reflected light.

10 6. The system of claim 1, wherein the sensor head further comprises a focusing optic for directing light emitted from the light source to the surface of the workpiece.

15 7. The system of claim 1, further comprising an optic configured to direct the portion of reflected light to the detector.

8. The system of claim 1, further comprising an archive for storing diameters and workpiece profiles.

9. The system of claim 1, wherein the memory further comprises an interface module for receiving user input and displaying diameters and the workpiece profile.

10. A method for determining the diameter measurements of a workpiece to generate a workpiece profile, the method comprising:

locating three parallel, lateral tracks on a surface of the workpiece, each track extending along a longitudinal length;

5 moving a sensor head along the three lateral tracks, wherein movement along each track is substantially continuous;

directing light from a single light source on the sensor head to the three lateral tracks along the longitudinal length;

measuring the intensity and position of a portion of reflected light from the surface of the workpiece along the three lateral tracks to determine proximity measurements;

determining the diameters of the workpiece along the longitudinal length based on the proximity measurements; and

generating a workpiece profile based on the diameters of the workpiece.

15 11. The method of claim 10 further comprising computing the slope of the workpiece along the longitudinal length.

12. The method of claim 10 further comprising:

20 measuring the intensity of a second portion of reflected light from the surface of the workpiece to determine a roughness measurement; and

computing the roughness of the surface of the workpiece based on the roughness measurement.

13. The method of claim 10 further comprising storing the workpiece profile in an archive.

14. The method of claim 10 wherein the light source comprises a laser light diode.

5

15. The method of claim 10 further comprising determining the location of a crown of the workpiece based on the workpiece profile.

16. The method of claim 10, further comprising focusing light emitted from the light source to the surface of the workpiece.

17. The method of claim 10, further comprising displaying diameters and a workpiece profile for the workpiece.

18. A computer readable medium having stored thereon computer executable instructions for performing a method for determining diameters of a workpiece to generate a workpiece profile, the method comprising:

locating three parallel, lateral tracks on a surface of the workpiece, each track extending along a longitudinal length;

moving a sensor head along the three lateral tracks, wherein movement along each track is substantially continuous;

directing light from a single light source on the sensor head to the three lateral tracks along the longitudinal length;

measuring the intensity and position of a portion of reflected light from the surface of the workpiece along the three lateral tracks to determine proximity measurements;

determining the diameters of the workpiece along the longitudinal length based on the proximity measurements; and

generating a workpiece profile based on the diameters of the workpiece.

19. The computer readable medium of claim 18 wherein the method further comprises computing the slope of the workpiece along the longitudinal length relative to the single light source.

20. The computer readable medium of claim 18, the method further comprising: measuring the intensity of a second portion of reflected light from the surface of the workpiece to determine a roughness measurement; and

computing the roughness of the surface of the workpiece based on the roughness measurement.

21. The computer readable medium of claim 18, the method further comprising storing  
5 the workpiece profile in a memory.

22. The computer readable medium of claim 18, the method further comprising  
determining the location of a crown of the workpiece based on the workpiece profile.

23. The computer readable medium of claim 20, the method further comprising  
displaying diameters and the workpiece profile.

24. A system for non-contact dimensional measurement of a workpiece rotated about a longitudinal axis, comprising:

processing means;

memory means coupled to the processing means and including sensor control means and

5 a wireframe means; and

sensing means movable in lateral, longitudinal, and transverse directions and in communication with the processing means, the sensing means including,

light source means for producing a light to contact a surface of the workpiece, and

detecting means for sensing a portion of reflected light from the workpiece, the

10 detecting means generating a signal indicative of the proximity of the workpiece,

wherein the sensor control means directs the sensing means to perform proximity measurements along three parallel, lateral tracks extending along a longitudinal length by moving the sensing means in proximity to and continuously along each lateral track,

wherein the wireframe means determines the diameters of the workpiece along the

15 longitudinal length based on the proximity measurements.